Safety Data Sheet

This safety data sheet was created pursuant to the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008
This SDS is for generic information purposes and does not reflect required country specific information for OEL

VINYCOL 170
Supercedes Date: 30-Nov-2016

Revision Date 25-Feb-2019
Revision Number 2.01

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier

Product Name VINYCOL 170
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesives.
Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Company Name
Bostik SA
420 rue d'Estienne d'Orves
92700 Colombes
FRANCE
Tel: +33 (0)1 49 00 90 00

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

Emergency Telephone No information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Serious eye damage/eye irritation	Category 2 - (H319)
Specific target organ toxicity (single exposure)	Category 3 - (H336)
Flammable liquids	Category 2 - (H225)

2.2. Label Elements

Contains: Methyl ethyl ketone, Acetone

Signal word
DANGER

Hazard statements
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
H225 - Highly flammable liquid and vapour

EU Specific Hazard Statements
EUH066 - Repeated exposure may cause skin dryness or cracking

precautionary statements
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray
P312 - Call a POISON CENTER or doctor if you feel unwell
P370 + P378 - In case of fire: Use dry chemical, CO2, water spray or alcohol-resistant foam to extinguish
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed
P501 - Dispose of contents/ container to an approved waste disposal plant
P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction
P403 + P235 - Store in a well-ventilated place. Keep cool

Additional information
Placed on the market in aerosol containers or in containers fitted with a sealed spray attachment.

2.3. Other Hazards

In use may form flammable/explosive vapour-air mixture

PBT and vPvB assessment

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical Name	EC No.	CAS No.	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Methyl ethyl ketone	201-159-0	78-93-3	>25 - <40	Eye Irrit. 2 (H319) (EUH066) STOT SE 3 (H336) Flam. Liq. 2 (H225)		01-2119457290-43-XXXX
Acetone	200-662-2	67-64-1	>25 - <40	Eye Irrit. 2 (H319) (EUH066) STOT SE 3 (H336) Flam. Liq. 2 (H225)		01-2119471330-49-XXXX

Full text of H- and EUH-phrases: see section 16
Note: ^ indicates not classifed, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. Get medical attention immediately if symptoms occur.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
Ingestion	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Clean mouth with water. Drink 1 or 2 glasses of water. Call a doctor or poison control centre immediately. Clean mouth with water and drink afterwards plenty of water.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	Burning sensation. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.
Unsuitable extinguishing media	Do not use straight streams. CAUTION: Use of water spray when fighting fire may be inefficient.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Hazardous Combustion Products	Carbon oxides.

5.3. Advice for firefighters

Special protective equipment for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate personnel to safe areas. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Avoid breathing vapours or mists. Ensure adequate ventilation. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in

	immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded.
Other information	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.
For emergency responders	Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions	Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not allow to enter into soil/subsoil.

6.3. Methods and material for containment and cleaning up

Methods for containment	Dyke far ahead of spill; use dry sand to contain the flow of material. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.
Methods for cleaning up	Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers. Take up mechanically, placing in appropriate containers for disposal.
Prevention of secondary hazards	Eliminate all ignition sources if safe to do so.

6.4. Reference to other sections

Reference to other sections	See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling	Use personal protection equipment. Avoid contact with skin and eyes. Avoid breathing vapours or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. In case of insufficient ventilation, wear suitable respiratory equipment.
General hygiene considerations	Keep away from food, drink and animal feedingstuffs. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations.

7.3. Specific end use(s)

Specific Use(s)
Adhesives.

Risk Management Methods (RMM)	The information required is contained in this Safety Data Sheet.
Other information	Observe technical data sheet.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Exposure Limits

Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.

Chemical Name	European Union
Methyl ethyl ketone 78-93-3	TWA: 200 ppm TWA: 600 mg/m³ STEL: 300 ppm STEL: 900 mg/m³
Acetone 67-64-1	TWA: 500 ppm TWA: 1210 mg/m³

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)	
Methyl ethyl ketone (78-93-3)	
Type	Worker Long term Systemic health effects
Exposure route	Dermal
Derived No Effect Level (DNEL)	1161 mg/kg bw/d
Type	Worker Long term Systemic health effects
Exposure route	Inhalation
Derived No Effect Level (DNEL)	600 mg/m³

Acetone (67-64-1)	
Type	Long term Systemic health effects Worker
Exposure route	Dermal
Derived No Effect Level (DNEL)	186 mg/kg bw/d
Type	Short term Local health effects Worker
Exposure route	Inhalation
Derived No Effect Level (DNEL)	2420 mg/m³
Type	Long term Systemic health effects Worker
Exposure route	Inhalation
Derived No Effect Level (DNEL)	1210 mg/m³

Derived No Effect Level (DNEL)	
Methyl ethyl ketone (78-93-3)	
Type	Consumer Long term Systemic health effects
Exposure route	Dermal
Derived No Effect Level (DNEL)	412 mg/kg bw/d

Type	Consumer Long term Systemic health effects
Exposure route	Inhalation
Derived No Effect Level (DNEL)	106 mg/m³

Type	Consumer Local health effects Systemic health effects
Exposure route	Oral
Derived No Effect Level (DNEL)	31 mg/kg bw/d

Acetone (67-64-1)	
Type	Consumer Long term Systemic health effects
Exposure route	Inhalation

Derived No Effect Level (DNEL)	200 mg/m³

Type	Consumer Long term Systemic health effects
Exposure route	Dermal
Derived No Effect Level (DNEL)	62 mg/kg bw/d

Type	Consumer Long term Systemic health effects
Exposure route	Oral
Derived No Effect Level (DNEL)	62 mg/kg bw/d

Predicted No Effect Concentration (PNEC) No information available.

Predicted No Effect Concentration (PNEC)	
Methyl ethyl ketone (78-93-3)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	55.8 mg/l
Marine water	55.8 mg/l
Freshwater sediment	287.74 mg/l
Marine sediment	287.7 mg/l
Soil	22.5 mg/l

Acetone (67-64-1)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	10.6 mg/l
Freshwater - intermittent	21 mg/l
Marine water	1.06 mg/l
Microorganisms in sewage treatment	100 mg/l
Freshwater sediment	30.4 mg/kg dry weight
Marine water	3.04 mg/kg dry weight
Soil	29.5 mg/kg dry weight

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/face protection Tight sealing safety goggles. Face protection shield.

Hand protection Wear protective gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature.

Skin and body protection Antistatic footwear. Wear fire/flame resistant/retardant clothing. Gloves made of plastic or rubber. Suitable protective clothing. Apron.

Respiratory protection In case of inadequate ventilation wear respiratory protection. In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

Recommended filter type: Organic gases and vapours filter conforming to EN 14387.

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical State Liquid
Appearance viscous
Colour Clear to light yellow
Odour Solvent
Odour Threshold No information available

Property	Values	Remarks • Method
pH	No data available	
Melting point / freezing point	No data available	
Boiling point / boiling range	56 °C	

Flash Point	-21 °C	CC (closed cup)
Evaporation Rate	No data available	
Flammability (solid, gas)	No data available	
Flammability Limit in Air		
Upper flammability or explosive limits	13	
Lower flammability or explosive limits	1.8	
Vapour Pressure	110	kPa
Vapour Density	No data available	
Relative Density	0.86 - 20	None known
Water Solubility	Insoluble in water	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
Kinematic Viscosity	No data available	
Dynamic Viscosity	2900 - 3500 mPa s	@ 20 °C
Explosive properties	No data available	
Oxidising properties	No data available	

9.2. Other information

Solid content (%)	>= 24.5	
Softening Point	No information available	
Molecular Weight	No information available	
VOC (volatile organic compound)	75.5 g/L	European directive n°2010/75/UE
Density	No information available	
Bulk Density	No information available	

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion Data

Sensitivity to mechanical impact	None.
Sensitivity to static discharge	Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product information .

Inhalation May cause irritation of respiratory tract. May cause drowsiness or dizziness.

Eye contact Causes serious eye irritation. May cause redness, itching, and pain.

Skin contact May cause irritation. Prolonged contact may cause redness and irritation.

Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms May cause redness and tearing of the eyes. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Numerical measures of toxicity

Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Methyl ethyl ketone 78-93-3	= 2483 mg/kg (Rat)	= 5000 mg/kg (Rabbit)	= 11700 ppm (Rat) 4 h
Acetone 67-64-1	= 5800 mg/kg (Rat)	>15800 mg/Kg (rat)	= 79 mg/l(Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation May cause skin irritation.

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity .

Chemical Name	Algae/aquatic plants	Fish	Toxicity to Micro-organisms	Crustacea	M-Factor
Methyl ethyl ketone 78-93-3	EC50=1972 mg/l (Pseudokirchneriella subcapitata)	LC50: 3130 - 3320mg/L (96h, Pimephales promelas)	EC50 = 3403 mg/L 30 min EC50 = 3426 mg/L 5 min	EC50 48 h > 308 mg/L (Daphnia magna)	-
Acetone 67-64-1	-	LC50 96 h 4.74 - 6.33 mL/L (Oncorhynchus mykiss)	EC50 = 14500 mg/L 15 min	EC50 48 h 10294 - 17704 mg/L (Daphnia magna Static)	-

12.2. Persistence and degradability

Persistence and degradability No information available.

Component Information			
Methyl ethyl ketone (78-93-3)			
Method	**Exposure time**	**Value**	**Results**
OECD Test No. 301D: Ready Biodegradability: Closed Bottle Test (TG 301 D)	28 days	biodegradation	98 % Readily biodegradable

12.3. Bioaccumulative potential

Bioaccumulative potential There is no data for this product.

Component Information

Chemical Name	Partition coefficient	Bioconcentration factor (BCF)
Methyl ethyl ketone 78-93-3	0.3	-
Acetone 67-64-1	-0.24	0.69

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment .

Chemical Name	PBT and vPvB assessment
Methyl ethyl ketone 78-93-3	The substance is not PBT / vPvB
Acetone 67-64-1	The substance is not PBT / vPvB

12.6. Other adverse effects

Other Adverse Effects No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products	Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Empty containers pose a potential fire and explosion hazard. Do not cut, puncture of weld containers.
European Waste Catalogue	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Note: The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments made in non-bulk packages (see regulatory definition).

Land transport (ADR/RID)

14.1 UN Number	UN1133
14.2 Proper Shipping Name	Adhesives
14.3 Transport hazard class(es)	3
Labels	3
14.4 Packing Group	II
Description	UN1133, Adhesives, 3, II, (D/E)
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	640C
Classification Code	F1
Tunnel restriction code	(D/E)
Limited Quantity (LQ)	5 L
ADR Hazard Id (Kemmler Number)	33

IMDG

14.1 UN Number	UN1133
14.2 Proper Shipping Name	Adhesives
14.3 Transport hazard class(es)	3
14.4 Packing Group	II
Description	UN1133, Adhesives, 3, II, (-21°C c.c.)
14.5 Marine Pollutant	Np
14.6 Special Provisions	None
Limited Quantity (LQ)	5 L
EmS-No.	F-E, S-D

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code No information available

Air transport (ICAO-TI / IATA-DGR)

14.1 UN Number	UN1133
14.2 Proper Shipping Name	Adhesives
14.3 Transport hazard class(es)	3
14.4 Packing Group	II
Description	UN1133, Adhesives, 3, II
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	A3
Limited Quantity (LQ)	1 L
ERG Code	3L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

EU-REACH (1907/2006) - Candidate List of Substances of Very High Concern (SVHC) for Authorization in accordance with Article 59
This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction
This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

EU-REACH (1907/2006) - Annex XIV - List of substances subject to Authorization
This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)
P5a - FLAMMABLE LIQUIDS
P5b - FLAMMABLE LIQUIDS
P5c - FLAMMABLE LIQUIDS

Ozone-depleting substances (ODS) regulation (EC) 1005/2009
Not applicable

Persistent Organic Pollutants
Not applicable

National Regulations

France

Occupational Illnesses (R-463-3, France)

Chemical Name	French RG number
Methyl ethyl ketone 78-93-3	RG 84
Acetone 67-64-1	RG 84

Germany

Ordinance on Industrial Safety and Health - Germany - BetrSichV
Flammable liquid (R11), EEC: refer to Annex III No. 1 (fire and explosion hazards) and § 7 paragraph 4

Netherlands

List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)
Not Listed

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
H225 - Highly flammable liquid and vapour
EUH066 - Repeated exposure may cause skin dryness or cracking

Legend
SVHC: Substances of Very High Concern for Authorisation:

Legend SECTION 8: Exposure controls/personal protection

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
STOT RE Specific target organ toxicity - Repeated exposure
STOT SE Specific target organ toxicity - Single exposure
EWC: European Waste Catalogue

Key literature references and sources for data
Classification and labeling data calculated from data received from raw material suppliers

Prepared By Product Safety & Regulatory Affairs

Revision Date 25-Feb-2019

Indication of changes

Revision note SDS sections updated: 2, 3, 11, 15.

Training Advice Provide adequate information, instruction, and training for operator

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer
The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet